

**AMENDMENTS TO THE CLAIMS**

**This listing of claims will replace all prior versions and listings of claims in the application:**

**LISTING OF CLAIMS:**

1. (currently amended): A node-search method in a network, comprising the steps of:  
a host of a first domain, acquiring a packet which includes routing information of a network configured with a plurality of domains including the first domain connected to at least one interworking unit;

the host, sending a broadcast packet, for requesting a response from a node which provides a specific service, to at least any one of said plurality of domains other than the first domain which is listed in said acquired routing information; and

receiving a response packet for said broadcast packet and detecting the node which sent the response packet,

wherein the host is a client device.

2. (currently amended): A node-search method in a network, comprising the steps of:  
sending a packet, for requesting routing information from the network which is connected to an interworking unit, from a ~~host~~client device of a first domain, to the interworking unit, where the interworking unit is capable of storing routing information set in advance and where the network is configured with a plurality of domains including the first domain;

receiving, in said ~~host~~client device, a packet containing said routing information;

sending a broadcast packet, for requesting a response from a node that provides a specific service, from said ~~host~~client device to at least any one of said plurality of domains other than said first domain which is listed in said received routing information; and

receiving, in said ~~host~~client device, a response packet in response to said broadcast packet, and detecting the node which sent the response packet.

3. (canceled)

4. (currently amended): A node-search method in a network, comprising the steps of:

a client device, receiving a RIP (Routing Information Protocol) packet;

the client device, acquiring information indicating a network number and an address of a router of each domain in the network from said received RIP packet; and

the client device, broadcasting, based on said acquired information, into a specific network so as to search for a node, using a specific port number.

5. (currently amended): A node-search device for searching for a node in a network, comprising:

network interface means for connecting with the network, where the network is configured with a plurality of domains including a first domain;

~~means~~ a client device of said first domain, ~~for~~ acquiring domain information from a packet containing routing information which was acquired by said network interface means;

means for finding broadcast addresses for said domains;

~~means for~~the client device, generating a request packet for requesting a response from a node which provides a specific service, and sending the packet to at least one of said plurality of domains other than said first domain which is listed in said acquired routing information; and

means of extracting information indicating nodes which perform said specific service, which is contained in a response packet to said request packet.

6. (currently amended): A node-search device of a first domain for searching for a node in a network, comprising:

~~means for sending~~a client device that sends a packet, for requesting routing information for a network configured with a plurality of domains including the first domain connected to at least one interworking unit, to the at least one interworking unit, which is capable of storing preset routing information;

~~means for~~the client device, receiving a packet containing said routing information and acquiring information indicating a node contained in said routing information;

~~means for~~the client device, sending a request packet, for requesting a response from a node which provides a specific service, which is broadcasted to at least any one of said plurality of domains other than the first domain connected through the interworking unit, to the interworking unit; and

means for receiving a response packet for said request packet and detecting the node which sent the response packet.

7. (currently amended): A computer-readable storage medium in which a program which is executed by a computer of a first domain for searching for a node in a network is recorded, wherein:

said program makes the computer of the first domain execute:

a process of acquiring a packet, in a client device, the packet containing routing information, from at least one interworking unit of a network configured with a plurality of domains including the first domain;

a process of sending a broadcast packet, from the client device, the broadcast packet for requesting a response from a node which provides a specific service, to at least any one of said plurality of domains other than the first domain which is listed in said acquired routing information, and

a process of receiving a response packet for said broadcast packet and detecting the node which sent the response packet.

8. (currently amended): A computer-readable storage medium in which a program which is executed by a computer of a first domain for searching for a node in a network is recorded, wherein:

said program makes the computer of the first domain execute:

a process of sending a packet, from a client device, the packet for requesting routing information from at least one interworking unit of a network configured with a plurality of

domains including the first domain, to the at least one interworking unit, which is capable of storing preset routing information set in advance;

a process of receiving, in the client device, a packet containing said routing information;

a process of sending, from the client device, a broadcast packet for requesting a response from a node which provides a specific service, to at least any one of said plurality of domains other than the first domain which is listed in said routing information; and

a process of receiving a packet in response to said broadcast packet, and detecting the node which sent the response packet.

9. (original) A storage medium in which a program is stored, according to Claim 8, wherein:

said interworking unit is a router.

Claims 10-12 (canceled)

13. (currently amended): A computer-readable storage medium in which a program which is executed by a computer for searching for a service providing node in a network configured with a plurality of domains is recorded, wherein:

said program makes the computer execute:

a process of receiving a RIP (Routing Information Protocol) packet;

a process of acquiring information indicating a network number and mail address of each domain in the network from said received RIP packet; and

a process of broadcasting, based on said acquired information, into a specific network so as to search for a node, using a specific port number,

wherein said computer is a client device.

14. (currently amended): A computer-readable storage medium in which a program which is executed by a computer of a first domain for searching for a service providing node in a network configured with a plurality of domains, wherein:

said program makes the computer execute:

a process of receiving an SNMP (Simple Network Management Protocol) packet from at least one router of a network configured with a plurality of domains including the first domain;

a process of acquiring information indicating a network number and an address of a router of each domain of said plurality of domains including the first domain in the network from the received SNMP packet;

a process of broadcasting into at least any one of said plurality of domains other than the first domain, based on said acquired information so as to search for a node, using a specific port number,

wherein said computer is a client device.

15. (previously presented) The node-search method of claim 1, wherein a plurality of interworking units exist in the network, wherein at least one of said plurality of interworking units is a bridge, a brouter, or a router.

16. (currently amended) ~~The node-search method of claim 15,~~ A node-search method in a network, comprising the steps of:

a host of a first domain, acquiring a packet which includes routing information of a network configured with a plurality of domains including the first domain connected to at least one interworking unit;

the host, sending a broadcast packet, for requesting a response from a node which provides a specific service, to at least any one of said plurality of domains other than the first domain which is listed in said acquired routing information; and

receiving a response packet for said broadcast packet and detecting the node which sent the response packet,

wherein a plurality of interworking units exist in the network, wherein at least one of said plurality of interworking units is a bridge, a brouter, or a router, and

~~the node-search method further comprising:~~

first sending the broadcast packet to at least one of said plurality of domains with the fewest hop counts.

Amendment under 37 C.F.R. § 1.116  
U.S. Application No. 09/544,544

17. (previously presented) The node-search method of claim 15, the node-search method further comprising:

first sending the broadcast packet to at least one of said plurality of domains with a hop count less than a specified number.